International Journal of Computational Research in Science and Technology
E-ISSN: 3108-0871, Volume 2 Issue 5
Sep-Oct- 2026, PP 01-06

Machines That Predict Their Own Failure: A Review of Self-Predictive Maintenance Using Sensors, Machine Learning And Digital Twins

Inamdar Mohammad Hadi Mohammad Shaker[1] Prof. C. A. Kolse[2] Prof. M. C. Kolse[3] Prof. S. K. Said[4]

Department Of Artificial Intelligence And Data Science Jaihind College Of Engineering Pune, Maharashtra, India

Abstract—Industrial operations increasingly demand reliable, uninterrupted machines, yet conventional maintenance depends on fixed schedules or on repairing faults after they occur, causing unexpected breakdowns, downtime and high costs. Self-predictive machines monitor their own health and forecast failures early enough to plan maintenance. This paper reviews the technologies that make such machines possible. It covers condition monitoring with vibration, temperature, current and acoustic sensors, signal processing and feature extraction, anomaly detection with autoencoders, fault diagnosis with machine learning and deep networks, and prognostics that estimate remaining useful life with recurrent and convolutional models. Digital twin technology, which maintains a virtual replica of the physical machine updated with live data, is examined as a way to simulate degradation and test maintenance decisions. Benchmark datasets for bearings and turbofan engines are discussed. A five-layer self-predictive machine architecture comprising sensing, edge processing, health analytics, digital twin and maintenance decision layers is proposed, with research gaps, objectives, a comparison of methods and challenges such as scarce failure data, changing operating conditions and explainability. The review concludes that combining sensing, learning and digital twins enables condition-based maintenance that reduces downtime and cost.

***Index Terms*—Predictive maintenance, prognostics and health management, remaining useful life, anomaly detection, digital twin, condition monitoring, Industry 4.0**

I. Introduction

When a critical pump, motor or compressor fails without warning, production can stop for hours or days. Replacing parts on a fixed schedule avoids some failures but wastes components that still have useful life. The ideal is a machine that knows its own condition and warns operators before it fails.

Condition-based and predictive maintenance aim at this ideal. Jardine *et al.* [1] reviewed machinery diagnostics and prognostics for condition-based maintenance, and Lei *et al.* [2] described the full prognostics pipeline from data acquisition to remaining useful life (RUL) prediction. Deep learning and digital twins have recently made such systems more accurate and practical.

This paper reviews these technologies and proposes an architecture for self-predictive machines.

II. Background and Fundamental Concepts

2.1 Maintenance Strategies

Fig. 1 compares reactive maintenance (repair after failure), preventive maintenance (fixed schedules), condition-based maintenance (act when indicators exceed limits) and predictive maintenance (forecast future failure).

International Journal of Computational Research in
Science and Technology
E-ISSN: 3108-0871, Volume 2 Issue 5
Sep-Oct- 2026, PP 01-06




Fig. 1. Maintenance strategies from reactive to predictive.

2.2 Digital Twins

A digital twin is a virtual model of a physical asset that is continuously updated with sensor data. Grieves and Vickers [3] introduced the concept to anticipate undesirable behaviour in complex systems, and Tao *et al.* [4] reviewed its use in industry for monitoring, simulation and optimization.

III. Literature Survey

Smith and Randall [5] analysed the widely used Case Western Reserve University bearing dataset and provided benchmark diagnostic results, noting that some fault cases are harder than commonly assumed. Nectoux *et al.* [6] presented PRONOSTIA, an experimental platform that runs bearings to failure and provides data for prognostics research. Saxena *et al.* [7] simulated turbofan engine degradation in the C-MAPSS dataset.

Zhao *et al.* [8] reviewed deep learning for machine health monitoring, covering autoencoders, CNNs and RNNs, and found that learned features outperform hand-crafted ones when sufficient data exist. Malhotra *et al.* [9] trained LSTM encoder–decoders on normal multi-sensor data and used reconstruction error to detect anomalies without failure labels.

For prognostics, Zheng *et al.* [10] used LSTMs and Li *et al.* [11] used deep CNNs to estimate RUL accurately on benchmark data. Carvalho *et al.* [12] systematically reviewed machine learning for predictive maintenance and found random forests, neural networks and SVMs to be most common. Table I summarizes these works.

TABLE I Summary of Literature Survey

Ref.	Method	Key Findings	Limitations
[1]	Review of diagnostics and prognostics	Foundations of CBM	Pre-deep-learning
[2]	Systematic prognostics review	Full pipeline to RUL	Survey only
[5]	CWRU bearing benchmark study	Benchmark diagnostic results	Laboratory faults
[6]	PRONOSTIA run-to-failure platform	Real degradation data	Bearings only
[9]	LSTM encoder–decoder anomaly detection	No failure labels needed	Threshold tuning
[8]	Review of deep learning for MHM	Learned features outperform hand-crafted	Data hungry
[10]	LSTM RUL estimation	Accurate degradation tracking	Simulated data
[4]	Digital twin in industry review	Twin-based monitoring and optimization	High build cost

International Journal of Computational Research in Science and Technology
E-ISSN: 3108-0871, Volume 2 Issue 5
Sep-Oct- 2026, PP 01-06

IV. Research Gap

Real failure data are scarce because machines rarely fail, limiting supervised learning.

Models trained under one operating condition often fail under others.

Digital twins are expensive to build and keep synchronized with the physical machine.

RUL predictions are rarely accompanied by confidence intervals or explanations.

Integration with maintenance planning and spare-parts management is limited.

4.1 Objectives

- **O1:** To review condition monitoring, diagnosis and prognostics techniques.
- **O2:** To examine anomaly detection and RUL estimation with machine learning.
- **O3:** To study the role of digital twins in predictive maintenance.
- **O4:** To propose a self-predictive machine architecture.
- **O5:** To identify challenges and future research directions.

4.2 Proposed System Architecture

The proposed architecture is shown in Fig. 2.




Fig. 2. Proposed self-predictive machine architecture.

4.3 Sensing Layer

Accelerometers, temperature sensors, current clamps and acoustic sensors are mounted on critical components.

4.4 Edge Processing Layer

An edge device filters signals, computes features such as RMS vibration, kurtosis and spectral peaks, and runs a lightweight anomaly detector.

4.5 Health Analytics Layer

Diagnostic models identify fault types, and prognostic models estimate RUL with uncertainty.

International Journal of Computational Research in Science and Technology
E-ISSN: 3108-0871, Volume 2 Issue 5
Sep-Oct- 2026, PP 01-06

4.6 Digital Twin Layer

A physics-informed virtual model of the machine is updated with live data and used to simulate how faults will progress under different loads.

4.7 Maintenance Decision Layer

Alerts, RUL estimates and recommended actions are sent to the maintenance system, which schedules work and orders parts.

V. Methodology and Working

Fig. 3 outlines the workflow. A common vibration health indicator is the root-mean-square value of a signal window

$$RMS = \sqrt{(1/N)\sum x_i^2} \quad (1)$$

and an anomaly score is the reconstruction error of an autoencoder trained on healthy data,

$$e = \|x - \hat{x}\|^2 \quad (2)$$

with alerts raised when e exceeds a threshold learned from normal operation. RUL models are evaluated with RMSE and with scoring functions that penalize late predictions more than early ones.




Fig. 3. Self-predictive maintenance workflow.

5.1 Comparative Analysis

Table II compares methods. Threshold rules are simple but late, classical ML diagnoses known faults well, deep anomaly detection needs no failure labels, deep RUL models give the earliest warnings, and digital twins add simulation and explanation.

TABLE II Comparison of Predictive Maintenance Methods

Method	Labels Needed	Warning Time	Explainability
Threshold rules	No	Short	High
Classical ML diagnosis	Yes	Medium	Medium
Autoencoder anomaly	No	Medium	Low–Medium
LSTM / CNN RUL	Run-to-failure	Long	Low
Digital twin	Physics + data	Long	High

5.2 Challenges and Future Scope

Table III summarizes challenges. Future directions include transfer learning across machines and conditions, physics-informed neural networks, federated learning across factories and generative models that synthesize realistic failure data.

TABLE III Challenges and Mitigation

Challenge	Mitigation
Scarce failure data	Anomaly detection; simulation; synthetic data
Changing conditions	Transfer learning; condition normalization
Twin synchronization	Continuous model updating
Uncertain RUL	Probabilistic models; intervals
Operator trust	Explanations linked to physical features

VI. Conclusion

Machines that predict their own failure turn maintenance from a reactive cost into a planned activity. The reviewed literature shows that sensor-based condition monitoring, unsupervised anomaly detection, deep RUL estimation and digital twins together enable early, accurate warnings. Addressing data scarcity, changing conditions and explainability will allow self-predictive machines to become standard in Industry 4.0 plants.

6.1 Acknowledgment

The authors express their sincere gratitude to the Department of Artificial Intelligence and Data Science, Jaihind College of Engineering, Pune, for providing the facilities, guidance and encouragement needed to carry out this work. The authors also thank the faculty members and colleagues whose valuable suggestions helped improve the quality of this review.

References

1. A. K. S. Jardine, D. Lin, and D. Banjevic, “A review on machinery diagnostics and prognostics implementing condition-based maintenance,” Mech. Syst. Signal Process., vol. 20, no. 7, pp. 1483–1510, 2006.
2. Y. Lei, N. Li, L. Guo, N. Li, T. Yan, and J. Lin, “Machinery health prognostics: A systematic review from data acquisition to RUL prediction,” Mech. Syst. Signal Process., vol. 104, pp. 799–834, 2018.
3. M. Grieves and J. Vickers, “Digital twin: Mitigating unpredictable, undesirable emergent behavior in complex systems,” in Transdisciplinary Perspectives on Complex Systems. Cham, Switzerland: Springer, 2017, pp. 85–113.
4. F. Tao, H. Zhang, A. Liu, and A. Y. C. Nee, “Digital twin in industry: State-of-the-art,” IEEE Trans. Ind. Informat., vol. 15, no. 4, pp. 2405–2415, 2019.
5. W. A. Smith and R. B. Randall, “Rolling element bearing diagnostics using the Case Western Reserve University data: A benchmark study,” Mech. Syst. Signal Process., vol. 64–65, pp. 100–131, 2015.
6. P. Nectoux et al., “PRONOSTIA: An experimental platform for bearings accelerated degradation tests,” in Proc. IEEE Int. Conf. Prognostics Health Manage. (PHM), 2012.
7. A. Saxena, K. Goebel, D. Simon, and N. Eklund, “Damage propagation modeling for aircraft engine run-to-failure simulation,” in Proc. Int. Conf. Prognostics Health Manage. (PHM), 2008, pp. 1–9.

8. R. Zhao, R. Yan, Z. Chen, K. Mao, P. Wang, and R. X. Gao, “Deep learning and its applications to machine health monitoring,” Mech. Syst. Signal Process., vol. 115, pp. 213–237, 2019.
9. P. Malhotra et al., “LSTM-based encoder-decoder for multi-sensor anomaly detection,” in Proc. ICML Anomaly Detection Workshop, 2016, arXiv:1607.00148.
10. S. Zheng, K. Ristovski, A. Farahat, and C. Gupta, “Long short-term memory network for remaining useful life estimation,” in Proc. IEEE Int. Conf. Prognostics Health Manage. (ICPHM), 2017, pp. 88–95.
11. X. Li, Q. Ding, and J.-Q. Sun, “Remaining useful life estimation in prognostics using deep convolution neural networks,” Reliab. Eng. Syst. Saf., vol. 172, pp. 1–11, 2018.
12. T. P. Carvalho, F. A. A. M. N. Soares, R. Vita, R. da P. Francisco, J. P. Basto, and S. G. S. Alcalá, “A systematic literature review of machine learning methods applied to predictive maintenance,” Comput. Ind. Eng., vol. 137, Art. no. 106024, 2019.